

# Badger Multi-Purpose ABC Dry Chemical (Fire Extinguishing Agent)

# 1. PRODUCT AND COMPANY IDENTIFICATION

Product Name

Badger Multi-Purpose ABC Dry Chemical (Fire Extinguishing Agent)

Other Trade Names

90% MAP, Ammonium Phosphate, Monoammonium Phosphate,

Premium ABC

Manufacturer/Supplier Badger Fire Protection

Address 944 Glenwood Station Lane, Suite 303

Charlottesville, VA 22901

USA

**Phone Number** (434)-964-3200 **Chemtrec Number** (800) 424-9300

(for emergencies only) (703) 527-3887 (International)

Revision Date: August 7, 2007

MSDS Date: January 15, 2007

This MSDS has been compiled in accordance with - EC Directive 91/155/EC - OSHA's Hazcom Standard (29 CFR 1910.1200)

# COMPOSITION/INFORMATION ON THE COMPONENTS

| Component Name Monoammonium Phosphate | <b>CAS#/Codes</b> 7722-76-1 EC#2317645 | Concentration<br>90 - 97% | R Phrases<br>None | EU Classification<br>None |
|---------------------------------------|--|---------------------------|-------------------|---------------------------|
| Mica                                  | 12001-26-2                             | 1 - 4%                    | None              | None                      |
| Clay                                  | 8031-18-3                              | 1 - 4%                    | None              | None                      |
| Amorphous Silica                      | 7631-86-9<br>EC#2315454                | <2%                       | None              | None                      |
| Dye                                   | NA                                     | <0.1%                     | None              | None                      |

# HAZARD IDENTIFICATION

#### **EU Main Hazards**

Non Hazardous Powder

## **Routes of Entry**

- Eye contact - Inhalation - Skin contact

# Carcinogenic Status

See Section 11 - Toxicity

### **Target Organs**

- Respiratory System - Skin - Eye

### **Health Effects - Eyes**

Contact for short periods of time may cause irritation.

#### **Health Effects - Skin**

Contact may cause mild irritation.

Revision Date: August 7, 2007 Page 1 of 6



# Badger Multi-Purpose ABC Dry Chemical (Fire Extinguishing Agent)

# 3. HAZARD IDENTIFICATION

## **Health Effects - Ingestion**

Ingestion is not an expected route of exposure.

#### **Health Effects - Inhalation**

May irritate the respiratory tract. May cause transient cough and shortness of breath.

# 4. FIRST AID MEASURES

#### **Eyes**

Immediately flood the eye with plenty of water of warm water for at least 15 minutes, holding the eye open. Obtain medical attention if soreness or redness persists.

#### Skin

Wash affected area with soap and water. Obtain medical attention if irritation persists.

#### Ingestion

Dilute by drinking large quantities of water and obtain medical attention.

#### Inhalation

Move victim to fresh air. Obtain medical attention immediately for any breathing difficulty.

#### **Advice to Physicians**

Treat symptomatically.

## FIRE FIGHTING MEASURES

#### **Extinguishing Media**

This preparation is used as an extinguishing agent and therefore is not a problem when trying to control a blaze. Use extinguishing agent appropriate to other materials involved. Keep pressurized extinguishers and surroundings cool with water spray as they may rupture or burst in the heat of a fire.

## **Unusual Fire and Explosion Hazards**

Pressurized containers may explode in heat of fire.

#### **Protective Equipment for Fire-Fighting**

Wear full protective clothing and self-contained breathing apparatus as appropriate for specific fire conditions.

# ACCIDENTAL RELEASE MEASURES

Sweep up or vacuum. Prevent skin and eye contact. Wear appropriate protective equipment.

# HANDLING AND STORAGE

Pressurized extinguishers should be properly stored and secured to prevent falling or being knocked over. Do not drag, slide or roll extinguishers. Do not drop extinguishers or permit them to strike against each other. Never apply flame or localized heat directly to any part of the extinguisher or plastic container. Store pressurized extinguishers and plastic containers away from high heat sources. Storage area should be: - cool - dry - well ventilated - under cover - out of direct sunlight

Revision Date: August 7, 2007 Page 2 of 6



# Badger Multi-Purpose ABC Dry Chemical (Fire Extinguishing Agent)

# EXPOSURE CONTROLS/PERSONAL PROTECTION

## **Occupational Exposure Standards**

Occupational exposure limits are listed below, if they exist.

Mica

ACGIH TLV: 3 mg/m3 TWA, measured as respirable fraction of the aerosol.

OSHA PEL: 20 mppcf, <1% crystalline silica

**Nuisance Dust Limit** 

OSHA PEL: 50 mppcf or 15 mg/m3 TWA, total dust

15 mppcf or 5 mg/m3 TWA, respirable fraction

#### **Engineering Control Measures**

Use with adequate ventilation. There should be local procedures for the selection, training, inspection and maintenance of this equipment. When used in large volumes, use local exhaust ventilation.

#### **Respiratory Protection**

Not normally required. Use dust mask where dustiness is prevalent, or TLV is exceeded.

#### **Hand Protection**

Not normally needed when used as a portable fire extinguisher. Use gloves if irritation occurs.

#### **Eye Protection**

Chemical goggles or safety glasses with side shields.

## **Body Protection**

Normal work wear.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

**Physical State** Powder Pale Yellow Color Odor Odorless **Specific Gravity** Not available **Boiling Range/Point (°C/F)** Not applicable Flash Point (PMCC) (°C/F) Not Flammable Solubility in Water Not applicable Vapor Density (Air = 1) Heavier than air. **Vapor Pressure** Not applicable Not applicable **Evaporation Rate** 

# 10. STABILITY AND REACTIVITY

#### **Stability**

Stable under normal conditions.

#### **Conditions to Avoid**

- Heat - High temperatures - Exposure to direct sunlight

#### **Materials to Avoid**

- Strong oxidizing agents - strong acids - sodium hypochlorite

Revision Date: August 7, 2007 Page 3 of 6



# Badger Multi-Purpose ABC Dry Chemical (Fire Extinguishing Agent)

# 10. STABILITY AND REACTIVITY

## **Hazardous Polymerization**

Will not occur.

### **Hazardous Decomposition Products**

- oxides of carbon - ammonia - oxides of phosphorus - nitrogen oxides

# 11. TOXICOLOGICAL INFORMATION

### **Acute Toxicity**

Low order of acute toxicity.

### **Chronic Toxicity/Carcinogenicity**

This product is not expected to cause long term adverse health effects.

Mica and clay may contain small quantities of quartz (crystalline silica) as an impurity. Prolonged exposure to respirable crystalline silica dust at concentrations exceeding the occupational exposure limits may increase the risk of developing a disabling lung disease known as silicosis. IARC found limited evidence for pulmonary carcinogenicity of crystalline silica in humans.

#### Genotoxicity

This product is not expected to cause any mutagenic effects.

## Reproductive/Developmental Toxicity

This product is not expected to cause adverse reproductive effects.

# 12. ECOLOGICAL INFORMATION

#### **Mobility**

No relevant studies identified.

# Persistence/Degradability

No relevant studies identified.

#### **Bio-accumulation**

No relevant studies identified.

#### **Ecotoxicity**

No relevant studies identified.

# 13. DISPOSAL

Dispose of container in accordance with all applicable local and national regulations. Do not cut, puncture or weld on or near to the container. No harm to the environment is expected from this preparation.

Revision Date: August 7, 2007 Page 4 of 6



# Badger Multi-Purpose ABC Dry Chemical (Fire Extinguishing Agent)

## 14. TRANSPORT INFORMATION

DOT CFR 172.101 Data

Not regulated

UN Proper Shipping Name

Not regulated

UN Class None
UN Number None
UN Packaging Group None

# 15. REGULATORY INFORMATION

#### **EU Label Information**

Classification and labelling have been performed according to EU directives 67/548/EEC and 99/45/EC including amendments.

## **EU Hazard Symbol and Indication of Danger.**

This preparation is not classified as dangerous.

## R phrases

None

#### S phrases

None.

## US REGULATIONS (Federal, State) and INTERNATIONAL CHEMICAL REGISTRATION LAWS

## **TSCA Listing**

This product contains ingredients that are listed on or exempt from listing on the EPA Toxic Substance Control Act Chemical Substance Inventory.

#### **EINECS Listing**

All ingredients in this product have not been verified for listing on the European Inventory of Existing Commercial Chemical Substances (EINECS) or the European List of New Chemical Substances (ELINCS).

## **DSL/NDSL (Canadian) Listing**

All ingredients in this product are listed on the Domestic Substance List (DSL) or the Non-Domestic Substance List (NDSL) or are exempt from listing.

#### **WHMIS Classification**

D2B

This product was classified in accordance with the hazard criteria of the Canadian Controlled Products Regulations and the MSDS contains all the information required by these regulations.

### MA Right To Know Law

All components have been checked for inclusion on the Massachusetts Substance List (MSL). Those components present at or above the de minimus concentration include: - Mica (12001-26-2) 1-4% - Amorphous Silica (7631-86-9) < 2%

## PA Right To Know Law

This product contains the following chemicals found on the Pennsylvania Hazardous Substance List: - Mica (12001-26-2) 1-4% - Amorphous Silica (7631-86-9) <2%

#### **NJ Right To Know Law**

This product contains the following chemicals found on the NJ Right To Know Hazardous Substance List: - Mica (12001-26-2) 1-4% - Amorphous Silica (7631-86-9) <2%

Revision Date: August 7, 2007 Page 5 of 6



# Badger Multi-Purpose ABC Dry Chemical (Fire Extinguishing Agent)

# 15. REGULATORY INFORMATION

#### **California Proposition 65**

This product does not contain materials which the State of California has found to cause cancer, birth defects or other reproductive harm.

## SARA Title III Sect. 302 (EHS)

This product does not contain any chemicals subject to SARA Title III Section 302.

#### SARA Title III Sect. 304

This product does not contain any chemicals subject to SARA Title III Section 304.

### SARA Title III Sect. 311/312 Categorization

- Immediate (Acute) Health Hazard

SARA Title III Sect. 313

This product does not contain any chemicals that are listed in Section 313 at or above de minimis concentrations.

## OTHER INFORMATION

#### **NFPA Ratings**

NFPA Code for Health - 1

NFPA Code for Flammability - 0

NFPA Code for Reactivity - 0

NFPA Code for Special Hazards - None

#### **HMIS Ratings**

HMIS Code for Health - 1

HMIS Code for Flammability - 0

HMIS Code for Reactivity - 0

HMIS Code for Personal Protection - See Section 8

#### **Abbreviations**

N/A: Denotes no applicable information found or available

CAS#: Chemical Abstracts Service Number

ACGIH: American Conference of Governmental Industrial Hygienists

OSHA: Occupational Safety and Health Administration

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit STEL: Short Term Exposure Limit

NTP: National Toxicology Program

IARC: International Agency for Research on Cancer

R: Risk S: Safety

## Prepared By: EnviroNet LLC.

The information contained herein is based on data believed to be accurate. However, no representation, warranty, or guarantee is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for its own particular use. Badger Fire Protection assumes no responsibility for personal injury or property damage resulting from use, handling or from contact with this product.

Revision Date: August 7, 2007 Page 6 of 6

# BADGERStandard BADGERExtra



# ABC Multipurpose Dry Chemical Stored Pressure Extinguisher Models

These fire extinguishers are economical and extremely versatile. They are ideal for tackling the majority of fire risks typically found in commercial, industrial and domestic applications.

Badger dry chemical extinguishing agents contain the highest percentage of essential base ingredients found in the fire extinguisher industry. "Multipurpose" agent models are suitable for use on Class A, B and C fires.

**BadgerStandard** models offer compliance and protection at a competitive price.

**BadgerExtra** models offer compliance and protection with premium features.



**BADGER**Standard

Economical

compliance

**BADGER**Extra
Compliance
with premium features

# **BADGER**Standard Features

- 2.5, 5, 10 and 20 pound models
- Multipurpose agent contains 90% M.A.P.
- Laser welded carbon steel cylinders
- Corrosion resistant epoxy powder paint finish
- Stainless steel hose band & nozzle retainer
- UL Listed & USCG Approved Meets D.O.T. requirements
- 12 Year periodic hydrostatic test interval
- 6 Year product warranty
- Available with hanger hook or brackets
- Machined aluminum valves
- · Aluminum handles and levers

## **BADGER***Extra* Features

- 2.5, 5, 10 and 20 pound models
- Multipurpose agent contains 90% M.A.P.
- Laser welded carbon steel cylinders
- Corrosion resistant epoxy powder paint finish
- Stainless steel hose band & nozzle retainer
- UL Listed & USCG Approved Meets D.O.T. requirements
- 12 Year periodic hydrostatic test interval
- 6 Year product warranty
- Available with hanger hook or brackets

#### Plus...

- Chrome plated brass valves
- Stainless steel handles and levers
- Large loop stainless steel pull pins with tether
- All models feature steel internal siphon tubes
- Plated brass hose couplings with hex fitting
- Rugged, heavy duty hoses
- Easy-to-read two piece nameplates

# **Technical Data:** ABC Dry Chemical Stored Pressure Extinguisher Models

| MODEL NUMBER              | BadgerExtr<br>B250M-WH | •                  | Chemical E              | xtinguishe<br>B5M-B | r Models<br>B5M-1       | B5M-1B           | B10M                     | B10M-1            | B20M                     | BadgerSt<br>250MB-1 | andard <b>AB</b> (<br>5MB-6H | -                | emical<br>10MB-8H        | 20MB-6H                  |
|---------------------------|------------------------|--------------------|-------------------------|---------------------|-------------------------|------------------|--------------------------|-------------------|--------------------------|---------------------|------------------------------|------------------|--------------------------|--------------------------|
| NOMINAL CAPACITY (LBS)    | 2.5                    | 2.5                | 5                       | 5                   | 5                       | 5                | 10                       | 10                | 20                       | 2.5                 | 5                            | 5                | 10                       | 20                       |
| (KILOGRAMS)               | 1.13                   | 1.13               | 2.27                    | 2.27                | 2.27                    | 2.27             | 4.54                     | 4.54              | 9.07                     | 1.13                | 2.27                         | 2.27             | 4.54                     | 9.07                     |
| UL FIRE RATING            | 1A-10B:C               | 1A-10B:C           | 3A-40B:C                | 3A-40B:C            | 2A-10B:C                | 2A-10B:C         | 4A-80B:C                 | 4A-80B:C          | 20A-120B:C               | 1A-10B:C            | 3A-40B:C                     | 3A-40B:C         | 4A-80B:C                 | 20A-120B:C               |
| AGENT FLOW RATE (LBS/SEC) | .31                    | .31                | .39                     | .39                 | .39                     | .39              | .51                      | .54               | .75                      | .31                 | .39                          | .39              | .51                      | .75                      |
| (KG/SEC)                  | .14                    | .14                | .17                     | .17                 | .17                     | .17              | .23                      | .24               | .34                      | .14                 | .17                          | .17              | .23                      | .34                      |
| EXTINGUISHING AGENT TYPE  | ABC                    | ABC                | ABC                     | ABC                 | ABC                     | ABC              | ABC                      | ABC               | ABC                      | ABC                 | ABC                          | ABC              | ABC                      | ABC                      |
| ITEM PART NUMBER          | 23462                  | 23384              | 23390                   | 23463               | 23464                   | 23466            | 23396                    | 23467             | 23497                    | 22430               | 22435                        | 22486            | 22603                    | 22682                    |
| VALVE MATERIAL            | BRASS                  | BRASS              | BRASS                   | BRASS               | BRASS                   | BRASS            | BRASS                    | BRASS             | BRASS                    | ALUMINUM            | ALUMINUM                     | ALUMINUM         | ALUMINUM                 | ALUMINUM                 |
| CYLINDER MATERIAL         | STEEL                  | STEEL              | STEEL                   | STEEL               | STEEL                   | STEEL            | STEEL                    | STEEL             | STEEL                    | STEEL               | STEEL                        | STEEL            | STEEL                    | STEEL                    |
| SHIPPING WEIGHT (LBS)     | 5.4                    | 5.8                | 10.4                    | 10.4                | 10.4                    | 10.4             | 18                       | 18                | 33                       | 5.4                 | 10                           | 10               | 17                       | 33                       |
| (KILOGRAMS)               | 2.47                   | 2.65               | 4.7                     | 4.7                 | 4.7                     | 4.7              | 8.16                     | 8.16              | 15                       | 2.4                 | 4.5                          | 4.5              | 7.71                     | 14.96                    |
| OPERATING PRESSURE        | 195 PSI                | 195 PSI            | 195 PSI                 | 195 PSI             | 195 PSI                 | 195 PSI          | 195 PSI                  | 195 PSI           | 195 PSI                  | 195 PSI             | 195 PSI                      | 195 PSI          | 195 PSI                  | 195 PSI                  |
| EXPELLANT                 | NITROGEN               | NITROGEN           | NITROGEN                | NITROGEN            | NITROGEN                | NITROGEN         | NITROGEN                 | NITROGEN          | NITROGEN                 | NITROGEN            | NITROGEN                     | NITROGEN         | NITROGEN                 | NITROGEN                 |
| TEMPERATURE RANGE (F)     | -40° to 120°           | -40° to 120°       | -40° to 120°            | -40° to 120°        | -40° to 120°            | -40° to 120°     | -40° to 120°             | -40° to 120°      | -40° to 120°             | -40° to 120°        | -40° to 120°                 | -40° to 120°     | -40° to 120°             | -40° to 120°             |
| (C)                       | -40° to 49°            | -40° to 49°        | -40° to 49°             | -40° to 49°         | -40° to 49°             | -40° to 49°      | -40° to 49°              | -40° to 49°       | -40° to 49°              | -40° to 49°         | -40° to 49°                  | -40° to 49°      | -40° to 49°              | -40° to 49°              |
| DISCHARGE TIME (SECONDS)  | 9.5                    | 9.5                | 14                      | 14                  | 14                      | 14               | 22                       | 22                | 28                       | 9.5                 | 14                           | 14               | 22                       | 28                       |
| DISCHARGE RANGE (FEET)    | 10 to 15               | 10 to 15           | 12 to 18                | 12 to 18            | 12 to 18                | 12 to 18         | 16 to 20                 | 16 to 20          | 16 to 20                 | 10 to 15            | 12 to 18                     | 12 to 18         | 16 to 20                 | 16 to 20                 |
| (METERS)                  | 3.14 to 4.6            | 3.14 to 4.6        | 3.7 to 5.5              | 3.7 to 5.5          | 3.7 to 5.5              | 3.7 to 5.5       | 4.9 to 6.1               | 4.9 to 6.1        | 4.9 to 6.1               | 3.14 to 4.6         | 3.7 to 5.5                   | 3.7 to 5.5       | 4.9 to 6.1               | 4.9 to 6.1               |
| UNIT HEIGHT (INCHES)      | 14.875                 | 14.875             | 15.25                   | 15.25               | 15.25                   | 15.25            | 18.94                    | 19.13             | 21.13                    | 14.87               | 15.25                        | 15.25            | 18.94                    | 21.13                    |
| (CENTIMETERS)             | 37.78                  | 37.78              | 38.7                    | 38.7                | 38.7                    | 38.7             | 48.1                     | 48.59             | 53.67                    | 37.78               | 38.7                         | 38.7             | 48.1                     | 53.67                    |
| UNIT WIDTH (INCHES)       | 5.5                    | 5.5                | 7.5                     | 7.25                | 7.25                    | 7.25             | 7.75                     | 8.13              | 9.25                     | 5.5                 | 7.25                         | 7.25             | 7.75                     | 9.25                     |
| (CENTIMETERS)             | 13.97                  | 13.97              | 18.41                   | 18.41               | 18.41                   | 18.41            | 19.68                    | 20.65             | 23.49                    | 13.97               | 18.41                        | 18.41            | 19.68                    | 23.49                    |
| UNIT DEPTH (INCHES)       | 3                      | 3                  | 4.25                    | 4.25                | 4.25                    | 4.25             | 5.25                     | 5.25              | 7.25                     | 3                   | 4.25                         | 4.25             | 5.25                     | 7.25                     |
| (CENTIMETERS)             | 7.52                   | 7.62               | 10.8                    | 10.8                | 10.8                    | 10.8             | 13.33                    | 13.33             | 18.41                    | 7.62                | 10.8                         | 10.8             | 13.33                    | 18.41                    |
| USCG APPROVAL             |                        |                    | Type A Size-II          | Type A Size-II      | Type A Size-II          | Type A Size-II   | Type A Size-II           | Type A Size-II    | Type A Size-II           |                     | Type A Size-II               | Type A Size-II   | Type A Size-II           | Type A Size-II           |
|                           | Type B:C Size-I        | Type B:C Size-I    | Type B:C Size-I         | Type B:C Size-I     | Type B:C Size-I         | Type B:C Size-I  | Type B:C Size-II         | Type B:C Size-II  | Type B:C Size-III        | Type B:C Size-I     | Type B:C Size-I              | Type B:C Size-   | Type B:C Size-           | II Type B:C Size-III     |
| USCG BRACKET              | MB-250<br>OPTIONAL     | MB-250<br>INCLUDED | MB-5<br><i>OPTIONAL</i> | MB-5<br>INCLUDED    | MB-5<br><i>OPTIONAL</i> | MB-5<br>INCLUDED | UB-10<br><i>OPTIONAL</i> | UB-10<br>OPTIONAL | UB-20<br><i>OPTIONAL</i> | MB-250<br>INCLUDED  | MB-5<br><i>OPTIONAL</i>      | MB-5<br>INCLUDED | UB-10<br><i>OPTIONAL</i> | UB-20<br><i>OPTIONAL</i> |

This information is subject to change without notice. Badger Fire Protection disclaims any liability for any errors or misinterpretation of the information contained therein. Contact Badger Fire Protection for your local distributor for assistance.

# **Distributed by:**



# **Badger Fire Protection**

4251 Seminole Trail • Charlottesville, VA 22911
Tel 800 446 3857 or 434 973 4361
Fax 800 248 7809 or 434 973 1589
www.badgerfire.com

